

200 Watt High Temp Industrial Power Supply

Product Description

This 200 watt, single output, high temp, low profile, ac to dc power supply is designed for applications requiring a very narrow profile and can operate in an extreme environment. The operating temperature range is -40° to +85° C (baseplate). This 200 watt industrial power supply can operate in an IP65/IP67 rated enclosure without airflow.

Product Features

- Calculated MTBF: >500,000 hours
- Operating Temperature Range: -40° to +85° C (Baseplate)
- Compact Size: 1.85" x 2.4" x 4.6"
- High Efficiency: ~88%
- UL60950-1, CSA60950-1 (cUL), EN60950-1, & CE (LVD)



Image displays unit with EMI filter & control board

AC Input

- Voltage Input Range: 90-264VAC (nominal range)
- Frequency: 47-440Hz
- Phase: Single Phase, 2 wire plus ground
- Input: Current: 2.3A (110VAC), 1.2A (220Vac) Typical
- Inrush Current: 20A (110VAC), 40A (220VAC)
- Power Factor Correction: .98 minimum, meets EN61000-3-2
- Start-Up Time: <500mSec (Output within regulation)
- Input Surge Voltage: Input transient suppression circuitry to protect power supply from permanent damage.

Output Selection Guide

Maximum Output Power: 200 Watts*

Model #:	Voltage	Max Current	Regulation	Ripple
HTIPS200-3.3	3.3Vdc	25 Amps	±3%	50mV pk-pk
HTIPS200-5	5.0Vdc	25 Amps	±3%	50mV pk-pk
HTIPS 200-9	9.0Vdc	16 Amps	±1%	120mV pk-pk
HTIPS200-12	12Vdc	12 Amps	±1%	120mV pk-pk
HTIPS200-15	15Vdc	10 Amps	±1%	150mV pk-pk
HTIPS200-19	19Vdc	10 Amps	±1%	150mV pk-pk
HTIPS200-24	24Vdc	8.3 Amps	±1%	240mV pk-pk
HTIPS200-28	28Vdc	7.1 Amps	±1%	240mV pk-pk
HTIPS200-36	36Vdc	5.5 Amps	±1%	240mV pk-pk
HTIPS200-48	48Vdc	4.1 Amps	±1%	240mV pk-pk

*Note: Output voltages lower than 19V have been derated.

DC Output Characteristics

- Line Regulation: $\pm 1.0\%$ typical
- Load Regulation: $\pm 0.5\%$ typical (No load to full load; nominal input)
- Output Ripple/Noise: 1% typical (P-P; nominal input; full load; 20MHz bandwidth)
- Set Point Accuracy: $\pm 2.0\%$ of output voltage (Nominal input; full load; 25°C)
- Transient Response: 250 uSec recovery to 1% for 25% step load range from 50% to 100%
- Overshoot: Turn-on and turn-off overshoot should not exceed 5% over nominal voltage.

Electrical Characteristics

- Efficiency: 88% Minimum (Measuring at 115Vac, full load and 25°C)
- Turn On Delay: 1 second maximum at 115 Vac
- Hold-Up Time: None
- Isolation Voltage:
 - Input to Output: 3000Vrms
 - Input to Baseplate: 2500Vrms
 - Output to Baseplate: 1500Vrms
- Isolation Resistance: 10Mohms (output to baseplate), 25°C ambient 70%RH
- Temperature Regulation: $\pm 2.0\%/^{\circ}\text{C}$ ($\pm .005\%/^{\circ}\text{C}$ max; over operating temp range)

Protection

- Over Current Limit: 105-140% of full load (Automatic recovery)
- Over-Voltage Protection: 125-145% of nominal output voltage (Latching)
- Short Circuit: Continuous. Auto-Recovery after short circuit condition is removed.
- Over Temperature Protection: The power supply is protected for over temperature conditions with thermal shutdown. Auto-Recovery when temperature returns to normal.

Environmental

- Operating Temperature: -40° to +85° C (Baseplate)
- Storage Temperature: -40° to 100° C
- Operating Humidity: 20% to 95% RH, Non-condensing
- Storage Humidity: 10% to 95% RH, Non-condensing
- Operating Altitude: Sea-level to 20,000 ft. in pressurized environment
- Vibration: Operating: 15g-RMS, random, tri-axial vibration for 1 hr
- Shock: Operating: 5G, half sine, 11msec, 3 axes. Non-Operating: 15G, half sine, 11msec, 3 axes.
- Conducted EMI: EN 55022 Class B compliant (May require additional components)
- Safety Certifications: cUL (UL60950-1/CSA60950-1), TUV (EN60950-1) & CE (LVD)
- Cooling: Conduction

Mechanical

- Outline Dimensions: 1.85" X 2.4" X 4.6" (H X W X L)
- Weight: ~6.5 oz. (185 grams)
- I/O Connectors: Terminal pins

Optional Control and Alarms

- Output Inhibit

Notes

- Product specifications subject to change without notice. All rights reserved.
- The information and specifications contained in this document are believed to be correct and accurate at the time of publication. DSC Power Solutions, Inc. accepts no responsibility for consequences arising from printing errors or inaccuracies pertaining to any use or application of this document.

Outline Drawing

