

2000 Watt - MGPS Series, Military Grade Power Supply Product Specification

Product Description

This product is a 2000 watt, single output, military grade power supply designed for electronic systems operating in harsh environments under adverse temperature conditions. It is intended for a single phase, AC power source and designed to meet applicable military standards for airborne, ground and shipboard applications.

Product Features

- Designed to meet MIL-STD-461/704/810/1399
- Wide Frequency Range: 47-440Hz
- Operating Temperature Range: -40° to +85°C
- Baseplate Mounting, Conduction Cooled

AC Input

- Voltage Input Range: 90-264Vac
- Frequency: 50/60/400Hz (47-440Hz)
- Phase: Single Phase, 2 wire plus ground
- Typical Input Current: 20.0A at 115Vac input, full load
- Power Factor Correction: 0.95 min @ 115Vac, full load. Designed to meet MIL-STD-1399, Section 300A (60Hz)
- Input Transient Protection: Designed to meet MIL-STD-704A/D (80Vdc for 100mSec)
- Input Surge Protection: Designed to meet MIL-STD-1275A/D (100Vdc for 50mSec)



Output Selection Guide

Model #:	Voltage	Max Current	Regulation	Ripple
MGPS2000-1P-12	12Vdc	166.0 Amps	±3%	120mV pk-pk
MGPS2000-1P-15	15Vdc	133.0 Amps	±3%	150mV pk-pk
MGPS2000-1P-24	24Vdc	83.3 Amps	±3%	240mV pk-pk
MGPS2000-1P-28	28Vdc	71.4 Amps	±3%	240mV pk-pk
MGPS2000-1P-36	36Vdc	55.5 Amps	±3%	240mV pk-pk
MGPS2000-1P-48	48Vdc	41.6 Amps	±3%	240mV pk-pk

Note: Alternate output voltages are available, consult factory for availability.

DC Output Characteristics (floating)

- Output Power: 2000 watts (maximum continuous power, may require derating for some low voltage outputs)
- Line Regulation: ±2.0% Typical
- Load Regulation: ±2.0% Typical (No load to full load; nominal input)
- Output Ripple/Noise: 1% Typical (pk-pk; nominal input; full load; 20MHz bandwidth)
- Set Point Accuracy: ±1.0% of Output Voltage (Nominal input; full load; 25°C)
- Transient Response: Output voltage returns to within 1% in less than 2.5mS for a 50% load change and the peak transient does not exceed 5%
- Overshoot: Turn-on and turn-off overshoot should not exceed 5% over nominal voltage

Electrical Characteristics

- Switching Frequency: 250KHz Fixed
- Efficiency: 88% Typical (Measuring at 115Vac and at full load)
- Turn On Delay: 25 to 500mS (To nominal output voltage)
- Isolation Voltage:
 - Input to Output: 2000Vrms
 - Input to Chassis: 1000Vrms
 - Output to Chassis: 500Vdc
- Isolation Resistance: 100Mohms (Input to output)
- Temperature Regulation: $\pm 0.005\%/^{\circ}\text{C}$ ($\pm 2.0\%/^{\circ}\text{C}$ max; over operating temp range)

Protection

- Over Current Limit: 115 to 130%. Auto-recovery after removal of overload condition
- Over-Voltage Setpoint: 108 to 125% of output voltage. Unit latched 1 minute, recycle AC input to reset
- Short Circuit: Auto-recovery after short circuit condition is removed
- Over Temperature Protection: The power supply is protected for over temperature conditions with thermal shutdown. Auto-Recovery when temperature returns to normal

Environmental

- Operating Temperature: -40° to $+85^{\circ}\text{C}$ (baseplate)
- Storage Temperature: -50° to $+100^{\circ}\text{C}$
- Operating Humidity: 5% to 90% RH, Non-condensing
- Storage Humidity: 5% to 95% RH, Non-condensing
- Operating Altitude: Sea-level to 40,000 ft.
- Shock & Vibration: Designed to meet MIL-STD-810G
- EMC Radiated & Conducted EMI: Designed to meet MIL-STD-461F

Cooling

- Conduction Cooling: Baseplate not to exceed $+85^{\circ}\text{C}$ for full rated output

Mechanical

- Enclosure: Metal chassis, Aluminum baseplate and enclosure, non-finish
- Outline Dimensions: 2.5" X 7.5" X 11.0" (H X W X L) – excluding I/O connectors
- Weight: ~ 5.0 lbs. (~ 2268 grams)
- AC Input Connector (J1): D38999 or EQ.
- DC Output Connector (J2): D38999 or EQ.

Optional Features, Controls or Alarms

- Consult factory

Note

- Product specifications subject to change without notice